

## Flexible Conduit UL REDUCED WALL STEEL

### Product Construction

- Category Jacket Description
  - Flexible PVC
  - Resistant to Oils and Mild Acids
  - Flame Retardant
  - Sunlight Resistant (UV)
  - Marked HD for "Heavy-Duty"

### Applications

- "Listed and marked for Direct Burial and in Poured Concrete
  - For containment of 1000 volt and lower potential circuits Suitable as a grounding conductor when used for circuits rated up to 20A for the 3/8 & 1/2 inch trade sizes and 60A for the 3/4 through 1-1/4 inch trade sizes in lengths six feet or less per NEC Article 250.118(6). Larger sizes require separate grounding conductor.
  - Installations in hazardous (classified) locations:
    - Class I Div. 2: Article 501.10 (B)(2) & 501.30 (B)
    - Class II Div. 1: Article 502.10 (A)(2) & 502.30 (B) Div. 2: 502.10 (B)(2)
    - Class III Div. 1: Article 503.10 (A)(3) & 503.30 (B) Div. 2: 503.10 (B)"

# Fittings and Accessories



Part #	Bend Radius	Package Qty	Nom. O.D.
UALT-3/8-100	4	100 FT COIL	0.71"
UALT-1/2-100	5	100 FT COIL	0.84"
UALT-3/4-100	6	100 FT COIL	1.03"
UALT-1-100	12	100 FT COIL	1.315"
UALT-2-1/2-25	30	100 FT COIL	2.875"
UALT-3-25	36	25 FT COIL	3.5"
UALT-3-1/2-25	43	25 FT COIL	4"
UALT-4-25	52	25 FT COIL	4.5"
UALT-1-1/4-50	15	50 FT REEL	1.66"
UALT-1-1/2-50	17	50 FT REEL	1.9"
UALT-2-50	22	50 FT REEL	2.375"