

Why Purchase Circuit Breakers from OmniCable?

Availability, Accessibility, Traceability



OmniCable has signed an agreement with Eaton® to serve as an authorized genuine source of their circuit breakers for electrical distributors.

AVAILABILITY

OmniCable now sells Siemens circuit breakers in addition to Eaton & Square D to electrical distributors providing them with authorized, safe, and reliable products through a single source. OmniCable is an extension of your warehouse with an extensive inventory of circuit breakers and accessories. Circuit breakers are available 24 hours a day, 365 days a year and shipped the same day.

ACCESSIBILITY

It is all about safety when purchasing an AUTHENTIC product from an AUTHORIZED source. Unauthorized sources rely on deception and aggressive pricing. Identifying counterfeit products is extremely difficult. They are made with inferior materials, inaccurate manufacturing processes, and without functional or safety testing.

TRACEABILITY

An authentic product is only sold through an authorized source who can provide full TRACEABILITY. Purchasing products from unauthorized sources significantly increases your risk of receiving counterfeit, altered, tampered, or refurbished products. Unauthorized sources cannot provide traceability.

Don't expose your company to increased RISK and LIABILITY by purchasing suspect products from unauthorized sources. Your business reputation is on the line, so don't put your customers in an unsafe environment and exposing your company to unnecessary liability. Products purchased through unauthorized sources do not carry the factory warranty which leaves the distribution channel open to liability.

Applications

Types of equipment where circuit breakers are installed - Commercial Switchboards, Panelboards, Motor Control Centers, and Control Panels/Enclosures. Residential Loadcenters and Meter Centers.



Series C

- G-Frame
Amperage Range: 15-100
- F-Frame (EHD, FDB, FD, HFD,
FDC, EDB, EDS, ED, EDH, EDC)
Amperage Range: 10-225
- JD-Frame
Amperage Range: 70-250
- K-Frame
Amperage Range: 100-400
- LD-Frame
Amperage Range: 300-600
- MDL-Frame
Amperage Range: 400-800

Series G

- EG-Frame
Amperage Range: 15-125
- JG-Frame
Amperage Range: 50-250
- LG-Frame
Amperage Range: 250-600
- NG-Frame
Amperage Range: 800-1200
- RG-Frame
Amperage Range: 1600-2500

Specialty Circuit Breakers

- Motor Circuit Protectors (MCP)
Amperage Range: 3-1200
- 600V Direct Current (DC)
Amperage Range: 15-3000
- Photovoltaic/Solar DC
Amperage Range: 30-600
- High Instantaneous Circuit Breaker
Amperage Range: 125-400
- Engine Generator
Amperage Range: 15-1200
- Definite Purpose (HVAC)
Amperage Range: 15-800

Miniature Circuit Breakers

- BAB-Frame
Amperage Range: 10-125
- QBH-Frame
Amperage Range: 15-125

Residential Circuit Breakers

- BR-Frame (Plug-in)
Amperage Range: 10-150
- CH-Frame (Plug-in)
Amperage Range: 10-125