


Cat HP J-Hook with BC Beam Clamp, Swivel



- Easy installation to beam flanges
- Swivels to support various directional runs of cable
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- Provides superior fill capacity and load rating over most other non-continuous cable support alternatives
- Rounded edges on J-Hooks provide proper bend radius support for high performance data cables
- Cost effective alternative to expensive cable tray
- Complies with EN 50174-2
- Meets ISO®/IECSM 14763-2, TIA 568-C and TIA 569-C

Material: Steel, Spring Steel
 Finish: Pre-galvanized, Armour



| Part Number | Area | Cable Capacity, Cat 5e | Cable Capacity, Cat 6 | Cable Capacity, Cat 6A | Diameter Ø | Flange Thickness FT | Static Load F | Approvals |
|-------------|-----------------------|------------------------|-----------------------|------------------------|------------|---------------------|---------------|-----------|
| CAT16HPBCB | 1.07 in ² | 20 | 15 | 10 | 1" | 1/2" Max | 60 lb | cULus® |
| CAT21HPBCB | 2.29 in ² | 50 | 40 | 25 | 1 5/16" | 1/2" Max | 60 lb | cULus® |
| CAT32HPBCB | 3.97 in ² | 90 | 60 | 35 | 2" | 1/2" Max | 60 lb | cULus® |
| CAT48HPBCB | 9.26 in ² | 200 | 150 | 80 | 3" | 1/2" Max | 60 lb | cULus® |
| CAT64HPBCB | 15.48 in ² | 330 | 220 | 140 | 4" | 1/2" Max | 60 lb | cULus® |

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7.

Cable capacity is calculated based on a 70% fill rate.