




Speed Link SLK with Hook



- Complete system includes wire, locking device and pre-assembled hook end fitting
- Hooks to a wide range of nVent CADDY fasteners
- Fastens to the building structure or hanging services by looping around and hooking to wire rope
- Easy to remove for applications requiring maintenance
- Spring latch helps provide secure connection
- Insert cable through hole and use bottom side of hook as an end stop
- Also available in Y-hook configuration



Material: Steel, Polypropylene, Zinc alloy

Finish: Electro-galvanized

Static Load Safety Factor: 5:1



Part Number	Wire Rope Length	A	B	C	Static Load F	Standard Packaging Quantity
Wire Rope Diameter: 1.5 mm						
SLK15L1	3.3'	2.3"	0.9"	1/4"	44 lb	20 pc
SLK15L2	6.6'	2.3"	0.9"	1/4"	44 lb	20 pc
SLK15L2R2	6.6'	1.89"	0.71"	0.18"	44 lb	15 x 2 pc
SLK15L3	9.9'	2.3"	0.9"	1/4"	44 lb	20 pc
SLK15L3R2	9.9'	1.89"	0.71"	0.18"	44 lb	15 x 2 pc
SLK15L5	16.4'	2.3"	0.9"	1/4"	44 lb	20 pc
SLK15L5R2	16.4'	1.89"	0.71"	0.18"	44 lb	15 x 2 pc
SLK15L7	22.9'	2.3"	0.9"	1/4"	44 lb	20 pc
SLK15L10	32.8'	2.3"	0.9"	1/4"	44 lb	20 pc
Wire Rope Diameter: 2.0 mm						
SLK2L1	3.3'	2.3"	0.9"	1/4"	100 lb	10 pc
SLK2L2	6.6'	2.3"	0.9"	1/4"	100 lb	10 pc
SLK2L2R2	6.6'	2.24"	0.79"	0.22"	100 lb	15 x 2 pc
SLK2L3	9.9'	2.3"	0.9"	1/4"	100 lb	10 pc
SLK2L3R2	9.9'	2.24"	0.79"	0.22"	100 lb	15 x 2 pc
SLK2L5	16.4'	2.3"	0.9"	1/4"	100 lb	10 pc
SLK2L5R2	16.4'	2.24"	0.79"	0.22"	100 lb	15 x 2 pc
SLK2L7	22.9'	2.3"	0.9"	1/4"	100 lb	10 pc
SLK2L10	32.8'	2.3"	0.9"	1/4"	100 lb	10 pc
SLK2L10R2	32.8'	2.24"	0.79"	0.22"	100 lb	15 x 2 pc

Height H	Width W	Thickness T	Angle a
2.15"	3/4"	1/2"	90° Max