Speed Link SLK with Loop






• Complete system includes wire, locking device and pre-assembled loop end fitting











- Wire rope wraps around structure and through loop for quick installation
- Ideal for attaching to purlins, beams and other structural members
- Works well in tight or confined spaces
- Loop attaches directly to pipe, ductwork or other hanging assemblies

Material: Steel, Polypropylene, Zinc alloy Finish: Electro-galvanized Static Load Safety Factor: 5:1









Part Number Wire Rope Length L F Wire Rope Diameter: 1.5 mm 4" 44 lb SLK15L1LP 3.3' 4" 44 lb SLK15L1LPR2 3.3' 4" 44 lb SLK15L2LP 6.6' 4" 44 lb	
SLK15L1LP 3.3' 4" 44 lb SLK15L1LPR2 3.3' 4" 44 lb SLK15L2LP 6.6' 4" 44 lb	
SLK15L1LPR2 3.3' 4" 44 lb SLK15L2LP 6.6' 4" 44 lb	
SLK15L2LP 6.6' 4" 44 lb	
SLK15L2LPR2 6.6' 4" 44 lb	
SLK15L3LP 9.9' 4" 44 lb	
SLK15L3LPR2 9.9' 4" 44 lb	
SLK15L5LP 16.4' 4" 44 lb	
SLK15L5LPR2 16.4' 4" 44 lb	
SLK15L7LP 22.9' 4" 44 lb	
SLK15L10LP 32.8' 4" 44 lb	
Wire Rope Diameter: 2.0 mm	
SLK2L1LP 3.3' 4" 100 lb	
SLK2L2LP 6.6' 4" 100 lb	
SLK2L3LP 9.9' 4" 100 lb	
SLK2L5LP 16.4' 4" 100 lb	
SLK2L7LP 22.9' 4" 100 lb	
SLK2L10LP 32.8' 4" 100 lb	
Height Width Thickness Angle	
Height Width Thickness Angle H W T a	
2.15" 3/4" 1/2" 90° Max	