




Speed Link SLK with Y-Hook



- Complete system includes wire, locking device and two pre-assembled hook end fittings
- Fastens to the building structure and hooks to hanging services and tray
- Spring latch helps provide secure connection
- Convenient design allows one hook to be temporarily detached for maintenance or to add cables to the tray
- Single drop with double hook provides increased stability to the system
- Also available in a single-hook end fitting configuration



Material: Steel, Zinc alloy, Polypropylene

Finish: Electro-galvanized

Static Load Safety Factor: 5:1

Wire Rope Diameter: 2 mm



Part Number	Wire Rope Length	Wire Rope "Y" Length YL	A	B	C	Static Load F
SLK2YH500L2	6.6'	19.6"	2.3"	0.9"	1/4"	100 lb
SLK2YH500L2R2	6.6'	19.6"	2.3"	0.9"	1/4"	100 lb
SLK2YH500L3	9.9'	19.6"	2.3"	0.9"	1/4"	100 lb
SLK2YH500L3R2	9.9'	19.6"	2.3"	0.9"	1/4"	100 lb
SLK2YH500L7	22.3'	19.6"	2.3"	0.9"	1/4"	100 lb
Height H	Width W	Thickness T	Angle a			
2.15"	3/4"	1/2"	90° Max			