




# Speed Link SLK with Y-Toggle



- Complete system includes wire, locking device and two pre-assembled toggle end fittings
- Attaches to clearance holes in a variety of structures or hanging devices
- Ideal for supporting lighting fixtures



Material: Steel, Zinc alloy, Polypropylene

Finish: Electro-galvanized

Static Load Safety Factor: 5:1



| Part Number                       | Wire Rope Length | Wire Rope "Y" Length<br>YL | A          | B     | Static Load<br>F |
|-----------------------------------|------------------|----------------------------|------------|-------|------------------|
| <b>Wire Rope Diameter: 1.5 mm</b> |                  |                            |            |       |                  |
| SLK15Y300L3                       | 9.9'             | 11.8"                      | 1.65"      | 0.31" | 44 lb            |
| SLK15Y300L3R2                     | 9.9'             | 11.8"                      | 1.50"      | 0.20" | 44 lb            |
| SLK15Y500L3                       | 9.9'             | 19.6"                      | 1.65"      | 0.31" | 44 lb            |
| SLK15Y500L3R2                     | 9.9'             | 19.6"                      | 1.50"      | 0.20" | 44 lb            |
| SLK15Y300L5                       | 16.4'            | 11.8"                      | 1.65"      | 0.31" | 44 lb            |
| <b>Wire Rope Diameter: 2.0 mm</b> |                  |                            |            |       |                  |
| SLK2Y300L2                        | 6.6'             | 11.8"                      | 1.65"      | 0.31" | 100 lb           |
| SLK2Y300L3                        | 9.9'             | 11.8"                      | 1.65"      | 0.31" | 100 lb           |
| SLK2Y300L3R2                      | 9.9'             | 11.8"                      | 1.65"      | 0.31" | 100 lb           |
| SLK2Y500L3                        | 9.9'             | 19.6"                      | 1.65"      | 0.31" | 100 lb           |
| SLK2Y300L5                        | 16.4'            | 11.8"                      | 1.65"      | 0.31" | 100 lb           |
| SLK2Y300L7                        | 22.9'            | 11.8"                      | 1.65"      | 0.31" | 100 lb           |
| SLK2Y300L10                       | 32.8'            | 11.8"                      | 1.65"      | 0.31" | 100 lb           |
| Height<br>H                       | Width<br>W       | Thickness<br>T             | Angle<br>a |       |                  |
| 2.15"                             | 3/4"             | 1/2"                       | 90° Max    |       |                  |